



Farmweld Free Access Stall.

Durable. Productive. Versatile.

When a Free Access Stall is what you want, Farmweld is your best choice! The Farmweld Free Access Stall offers sows the safety and comfort of eating without interruption from other more dominant sows. It also allows for a private retreat for the sow when she needs to escape the busy gestation environment. While not eating or relaxing, the sow can back out of the stall and join the community of other sows.

The Farmweld Free Access Stall design allows for the back gate to be locked providing workers access to the animal, making inseminating and checking sows easy and safe. Gates in both the front and rear of the crate make it easy to move sows in and out of the stall. You can count on Farmweld's Free Access Stall to stand up to the rigors of housing sows year after year.



sow comfort, durable, easy access

F A R M W E L D F R E E A C C E S S S T A L L

Farmweld Free Access Stall sides feature solid-rod construction for durability and longevity. Standard rods are 3/4" (19 mm) top and bottom rods and 5/8" (16 mm) inner rods. For added insurance, the bottom 7" (178 mm) of the stall comes standard with stainless steel bottom straps and legs.



The Farmweld Free Access Stall features a back gate that offers the sow privacy when needed as well as the option to return to the community environment.

Low-rise feed trough is designed for durability, and at 3 1/2" (89 mm), the height maximizes sow comfort. Made of #304 stainless steel to resist corrosion, the feed trough won't leak and is easy to clean. Trough sizes available include: 10" (254 mm), 12" (305 mm) and 16" (407 mm). Bolt-on, galvanized feed tube includes stainless steel hardware to resist corrosion.

Select the size to best fit your needs. Stalls are available in 22" (559 mm) or 24" (610 mm) on center and a standard 7' (2.13 m) length. Other lengths are available upon request.

Farmweld additionally offers breeding equipment, including gating, to complete the package.

Durable, high-quality materials result in uniform heavy welds that ensure longevity of the gating as well as enhance the safety of workers and pigs alike. The gating weighs 13 pounds per foot (5.9 kg per 305 mm).

Gates are sized to fit your buildings. All gates are made according to your need and to fit each individual barn. That means there is no cutting or welding required on site.

Gating is designed with durability in mind for breeding stock - tall and rugged to withstand abuse. The breeding gating's overall height is 39" (991 mm) with 1" (25.4 mm) solid horizontal top and bottom rods and 1/2" (13 mm) solid inner rods on 4 1/4" (108 mm) centers.

On-site installation is quick and easy. The gating comes with all the hardware needed for complete installation on site. The standard package includes posts with 1/2" (13 mm) x 5" (127 mm) x 14" (356 mm) steel base plates.



Vertical rods keep pigs from climbing.

Gates can be turned upside down to give twice the life.

Posts provide extra durability. Posts are placed at the gating intersections to add stability and strength to the overall gating system.

Contact us for more information on the Farmweld Free Access Stall or any of our other products.



© 2024 Farmweld, Inc.

605 East Main Street, P.O. Box 520, Teutopolis, IL 62467

farmweld.com

Call us at **800-EAT-PORK**
(328-7675)